



AuditMatic Handheld Client

The AuditMatic Handheld Client includes a barcode scanner, RFID scanner, and 3MP camera as well as Ethernet, WIFI, GSM and Bluetooth communication capability all in a rugged IP65 construction. It allows you to tackle the most demanding AuditMatic applications with confidence.

Model and Part Numbers:

- **AUD-6000E-NUM:** AuditMatic Handheld Computer with Numeric Keyboard
- **AUD-6000E-QWERTY:** AuditMatic Handheld Computer with QWERTY Keyboard
- **AUD-SINGLE DOCK:** Single Slot Ethernet Charge Dock
- **AUD-QUAD DOCK:** Four Slot Ethernet Charge Dock
- **AUD-3YR-ACC:** Comprehensive 3-Year Handheld Warranty

Accessories:



Specifications

Physical Characteristics:

- Dimensions (W x H x D): 3.1 x 6.3 x 1.4 inch
- Weight (including battery): 14.3oz
- Display: 3.5" VGA TFT Touch Screen LCD with backlight
- Touch Panel: Analog resistance type
- Keypad Option: Numeric or QWERTY
- Battery: Rechargeable, 3.7V, 4400mAh, Li-ion
- Expansion: MicroSD slot
- SIM Slot: 1 SIM
- Ethernet: Supported with optional Ethernet cradle
- Camera: 3 megapixel autofocus camera with LED flash
- GPS: Integrated Assisted-GPS (A-GPS)

Performance Characteristics:

- CPU: PXA 320, 806MHz
- OS: Windows Mobile 6.1
- Memory: 256MB RAM / 512MB ROM
- Interface: RS-232C, USB 1.1 Host & Client

User Environment Characteristics:

- Operating Temp: -20C to 55C / -4F to 131F
- Storage Temp: -25C to 70C / -13F to 158F
- Humidity: 5% to 95% non-condensing
- Drop Spec: 6ft. / 1.8m drop to steel surface, 2 drops per 6 sides
- Rain / Dust Protection: IP65

Integrated Radios:

- WWAN: GSM / HSDPA (850, 900, 1800, 1900 and 2100 MHz)
- WLAN: IEEE 802.11b/g
- WPAN: Bluetooth Class II V2.0 + EDR, IrDA 1.2

Data Capture:

- Barcode: 1D & PDF417 Laser Class II or 1D & 2D CMOS Imager
- RFID: Integrated RFID, ISO 14443 A/B, ISO 15693

MIL-STD-810F Tested:

- Drop, Vibration, Shock, Ingress, Temperature, Altitude, Humidity